

# PCIe 4.0 SSD Storage Platform

for Datacenter Servers and Storage Arrays

## Turnkey Storage Solution with FLASH Controller, Customizable Firmware, and SSD Designs

FADU's PCIe 4.0 NVMe SSDs are designed to meet the increasing demands placed on Hyperscaler, Hyper-converged, Enterprise, and Edge data centers.

At the heart of FADU's SSDs is an innovative SSD controller architecture that enables ultra-low and consistent latency while virtually eliminating thermal throttling issues. As a result, FADU SSDs deliver industry leading KIOPS/Watt performance while supporting superior QoS.

It consumes up to 30% less power and operates up to twice as fast as other PCIe 4.0 SSDs, leading to the industry's best IOPS/Watt.

The SSDs support a variety of features for modern data centers, including hardware-based security, advanced telemetry, data path, and power loss protection.

FADU's PCIe 4.0 SSD Platform is based on industry standard specifications including NVMe 1.4b, PCIe 4.0 x 4, and OCP NVMe Cloud SSD 1.0a.

### Storage Platform

DELTA

### Interface

PCIe 4.0 x 4

### Specifications

NVMe 1.4b | OCP NVMe Cloud SSD 1.0a

### FLASH Controller

FADU FC4121

### SSD Designs

E1.S | U.2 Form Factors  
1TB | 2TB | 4TB | 8TB Capacities

### SSD Performance Up To


Sequential Read	7,050 MB/s
Sequential Write	4,200 MB/s
Random Read	1,350 KIOPS
Random Write	200 KIOPS

### SSD Power Consumption

Active: <14.5W Idle: <3.5W

### Benefits

- Twice the throughput of FADU's PCIe 3.0 SSDs
- Industry-leading KIOPS/Watt with up to 25% lower power than other PCIe 3.0 SSDs
- Consistent, low latency for superior Quality of Service (QoS) up to 9x better than most industry leading SSDs
- Leading edge, trusted industry security standards



E1.S



U.2



FC4121 Controller

## PCIe 4.0 SSD Specifications

FADU PCIe 4.0 SSDs deliver industry-leading performance at low power for higher sustained QoS at low latency.

Specifications		PCIe 4.0 SSDs					Notes
Interface		PCIe 4.0 x 4					
NVMe		NVMe 1.4b					
OCP Compliance		OCP NVMe Cloud SSD 1.0a					
Controller		FADU FC4121					
NAND		SKH V6 128 Layer 4D eTLC					
Form Factor		U.2 (15mm) - Enterprise SSD Form Factor					
		E1.S (5.9mm/9.5mm/15mm/25mm) - Enterprise Datacenter SSD Form Factor (EDSFF) optimized for 1U platforms					
U.2. and E1.S Performance		OP 7			OP 28		
Capacity (GB)		960	1,920	3,840	7,680	6,400	
Sequential Read (MB/s)		6,850	7,050	7,050	7,050	7,050	Queue Depth = 128 IO Size = 128KB
Sequential Write (MB/s)		1,750	3,100	4,200	4,200	4,200	
Random Read (KIOPS)		1,100	1,350	1,350	1,350	1,350	Queue Depth = 128 IO Size = 4KB
Random Write (KIOPS)		50	135	185	200	390	
Random Read Latency (µs)		70	70	70	70	70	Queue Depth = 1 IO Size = 4KB
Random Write Latency (µs)		20	15	15	15	15	
QoS (99.9%) Random Read (µs)		110/350	110/250	110/240	110/240	110/240	Queue Depth = 1/64 IO Size = 4KB
QoS (99.9%) Random Write (µs)		100/1900	30/1200	30/800	30/800	30/400	
Power Consumption							
U.2	Active Write (W)	< 7.5	< 10.5	< 13.0	< 14.5	< 14.5	
	Active Read (W)	< 8.5	< 9.5	< 10.5	< 12.5	< 12.5	
E1.S	Active Write (W)	< 7.5	< 10.0	< 12.5	< 13.5	< 13.5	
	Active Read (W)	< 8.5	< 9.5	< 10.5	< 12.5	< 12.5	
Idle (W)		< 3.5					
Reliability							
MTBF (Hour)		2.5 M					
UBER		1 Sector per 10 <sup>17</sup> Read					
Retention		3 Months @ 40°C (EOL)					
Warranty							
DWPD		0.85	1.0		3.0		
Period		5 Years					
Operating Temperature (°C)		0 ~ 70					

## PCIe 4.0 SSD Security Features

PCIe 4.0 SSDs offer state-of-the-art security features to ensure data integrity in Hyperscaler, Hyper-Converged, Enterprise, and Edge data center storage.

Security Features	Benefit
Data-path E2E Protection (SECDED)	End-to-end data protection ensures the integrity of data transmission along the entire pathway from the host to the SSD storage medium
Internal RAID	Supports internal redundant array of independent disks to protect data
Self Encrypting Drive (AES-XTS)	Self-encrypting drives (SEDs) provide strong data encryption on the fly without performance degradation
Secure Boot	Supports secure boot to prevent malicious software from loading at start up
TCG/TCG OPAL 2.01	Supports Trusted Computing Group OPAL standards

## PCIe 4.0 SSD Data Center Features

PCIe 4.0 SSDs are designed for streamlined and standardized monitoring and management in scalable data center environments with a high degree of configurability, reducing the total cost of ownership.

Data Center Features	Benefit
Multiple Namespaces (NS)	Data center level requirement support (Max 128NS)
SMART / Health Log / Telemetry Log	Fully supports all OCP log requirements, providing data center-level monitoring and debugging capabilities
Latency Monitoring Feature	Addresses bottlenecks and performance issues quickly and efficiently
NVMe-MI 1.0a / Vital Product Data (VPD) over SMBus Supported	Standardized SSD monitoring system support for Enhanced and Streamlined Maintenance
Power Loss Protection (PLP)	Ensures data is not lost while the SSD is writing data during a power failure
Multiple Sector Size Support	Support for 512 and 4096-byte sectors to satisfy multiple platforms, various workloads, and operating systems